UNCLASSIFIED

AD NUMBER AD146463 CLASSIFICATION CHANGES TO: UNCLASSIFIED FROM: CONFIDENTIAL LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 27 SEP 1957.
Other requests shall be referred to Aberdeen Proving Ground, MD.

AUTHORITY

APG D/A, 19 Nov 1980; APG D/A, 19 Nov 1980

THIS REPORT HAS BEEN DELIMITED

AND CLEARED FOR PUBLIC RELEASE

UNDER DOD DIRECTIVE 5200.20 AND

NO RESTRICTIONS ARE IMPOSED UPON

ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD 146463

TO: UNCLASSIFIED
FROM CONFIDENTIAL
AUTHORITY:

- APG, Frete, 19 Nov 80



UNCLASSIFIED



Armed Services Technical Information Agency Reproduced by

DOCUMENT SERVICE CENTER

KNOTT BUILDING, DAYTON, 2, OHIO

FOR

MICRO-CARD

CONTROL ONLY

1 OF 1

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U.S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAND DEAWINGS, SEECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.





Aberdeen Proving Ground

MARYLANDREFERENCE COPY

STATIC PENETRATION TESTS OF

120MM, T153, HEAT SHELL(U)

3.4 ... PA 183

D. A. Project No. 504-03-050'

Regracition to Report OCO Project No. TA1-1602

ANY ASTROCEN PROVING SHOUND, NO. 415

This document is the property of the United States
Government. It is furnished for the duration of the contract and
shall be returned when no longer required, or upon
recall by ASTIA to the following address:
Armed Services Technical Information Agency, Document Service Center,
Knott Building, Dayton 2, Ohio.

NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.

THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

REFERENCE COPY

DEVELOPMENT AND PROOF SERVICES
ABERDMEN PROVING GROUND
MARYLAND

CONFIDENTIAL

AUTHORITY: PESD No. 70405530-01-10902

Pvt.JGNelson/ncj 27 September 1957

STATIC PENETRATION TESTS OF

CODE SEEL ACTIONS

1201M, T153, HEAT SHELL

EIGHTEENTH REPORT ON ORDNANCE PROJECT NO. TA1-1602

DATES OF TEST: 25 - 27 JUNE 1957

ABSTRACT

OBJECTIVE

To determine the static penetration of standard T153ES shell with and without the spike, and the comparative penetration of five new T153 designs.

SUMMERY

Five rounds each of 120mm, HEAT Shell (Model Numbers T153-ST14, T153-ST15, T153-ST16, T153-ST17, T153-ST18, T153-ST19, T153-ST20), were statically fired atop stacks of 28 each - 8° x 8° x $1-1/32^{\circ}$ homogeneous armor plate to observe total penetration, hole dimensions (entrance and exit), and unusual hole patterns.

The average penetration for each design was: T153-ST14 - 17.30"; T153-ST15 - 20.07"; T153-ST16 - 17.72"; T153-ST17 - 19.72"; T153-ST18 - 18.06"; T153-ST19 - 16.96" (Std. with spike); and T153-ST20 - 17.94" (Std. without spike).

CONCLUSION

It is concluded from static firings that the T153-ST15 and T153-ST17 will produce the greatest armor penetration of the designs tested.

RECOMMENDATIONS

It is recommended that:

All seven designs be tested for dynamic penetration of armor by firing up to 2000 yards at homogeneous armor plate at predetermined degrees of obliquity.

Designs T153-ST15 and T153-ST17 be considered as having produced the greatest armor penetration (by static firing) of the designs tested.

REGRADING DATA CANNOT BE PREDETERMINED

45519

CONTENTS

																				1	Page No.
INTRODUCTION					•	0	•		•	0				•	•	0	0		•	•	3
DESCRIPTION	OF MAT	YERTEL.	• •	0	•		0	•	•	•	0 •			0	0	•	•		•	•	3
DETAILS OF T	est .			0	•		•	•	0		• •		0		•	•	•	•	•	•	4,
CONCLUSIONS			0 0	0	0 0	•	•	o	•	0	0 0	٠	•	•		•	•	٠	•	0	6
R ECOMMENDATI	ons .	6 0 0	0 0		0 0	٠	•	0	0	•	• 0		•		•		•	•	•	•	6
REFERENCES .	0 0 0			•	0 0	0			•	u :		•		c		•	0	•	•	•	8
OBSERVERS .		0 00 0	0 6	o	0 0	0	٥	0	٥		0 6	ō.	0	0	0	•	0	9	0	٠	8
APPENDIX A -	Corre	:epixoge	103	•		0			•	0	υ •	9		0	v	٠	9	s	•	•	A-l
APPENDIX B -	Round	l-by-Ro	und !	De.t	å.	į		0	•	•		•	•	•	•	•	•	•	•	•	B-1
APPENDIX C -	Eurosa	donante.	l Am	MU.	dti	.00.2	De	ta	C	27	de	•	•	•	•	•	•	•	•	•	C-1
APPENDIX D -	Dista	ibuti o	2 .	•		0		0				٠		•	•	•	•	•	•	•	D-1

I IMPRODUCTION

- A. In 1950 Picatinny Arsenal was assigned technical supervision of the development of the 120mm, T153, HEAT round. The program was suspended in Jamuary 1956 at 80 percent completion and was resumed in August 1956 with June 1957 as the target completion date. Frankford Arsenal has since been given the technical supervision of the program; also, negotiations of a contract to complete the development have been finished.
- B. The round is required to defeat 16-inch armor plate with maximum behind-the-plate affect at a range of 2000 yards. The existing problem areas are thought to be:
 - 1. Imadequate wiring system.
 - 2. Inadequate fuzing.
 - 3. Inadequate "lucky" mounting system.
 - 4. Inadequate space in spike to permit jet formation.

II DESCRIPTION OF MATERIEL

Item	Quantity	Component	Dwg. No.	Remarks
1	5	T153-ST20	WBSK-1342	T153E8 without Spike.
2	5	T153-ST19	WBSK-1342	Tl53E8 w/o tapered wire, w/spike.
3	5	T153-ST14	WBSK-1342	Large diameter spike, comented joints.
4	5	T153-ST18	WBSK-1342	Spike large diameter, closed at nose end, all wire con- nections made at base of shell.
5	5	T153-6T16	WBSK-1342	Medium diameter spike, cemented joints.
6	5	T153-8T15	WBSK-1342	Same as ST16 except wire passes through cone near apex.
7	5	T153-8T17	WBSK-1342	Same as ST15 except "snap-in" cone.

Drawing No. WBSK-1342 is included as Figure 1.

CONFLUENTIAL




Figure 1 - Dwg. No. WBSK 1342

III DETAILS OF TEST

- A. Five rounds each of the seven designs in question were set up for firing in the following manner:
- 1. For each round a stack of 28 each $8^{m} \times 8^{m} \times 1-1/32^{m}$ homogeneous armor plate was made.
- 2. Cardboard tube "standoffs" were taped to the round and to the top plate of the stack to assure no "blow-over" or wobbling previous to firing.
- 3. The rounds were armed with Tetryl pellets $1-1/4^n$ diameter by $1/2^n$ high and detonated by Engineer's special blasting caps inserted in centered holes in $1-1/4^n$ diameter by one inch high hard wood blocks.




Figure 2 - B25378: Typical example of setup of subject round immediately before firing. Round is taped to cardboard stand-off tube which is taped to top plate of stack of 28 each 8"x8"x1" plates.

- B. Measurements (to the nearest 1/16") were taken of the entrance and exit hole in each plate. Observations of jet location, hole shape (unusual), and unusual occurrences were also recorded.
- C. By eliminating the rounds that both showed defect upon I-Ray and produced a penetration discrepancy greater than one inch, the following average penetrations for each design tested were determined:

T153-ST14 - 17.30**
T153-ST15 - 20.07**
T153-ST16 - 17.72**
T153-ST17 - 19.72**
T153-ST18 - 18.06**
T153-ST19 - 16.96**
T153-ST20 - 17.94**

D. It should be noted that there are four different external shapes represented in the seven designs tested. Therefore, it is possible and highly probable that the aerodynamic characteristics of the four external shapes are quite different. Hence, discrepancies among the four designs in accuracy, terminal velocities, flight stability and dynamic plate penetration may be realized.

IV CONCLUSIONS

It is concluded that:

- A. The T153-ST15 and T153-ST17 will produce the greatest armor penetration (by static firing) of the designs tested.
- B. The average penetration of all seven designs was considered to exceed (statically) the military requirement of armor 16 inches thick.

V RECOMMENDATIONS

It is recommended that:

- A. All seven designs be tested for dynamic penetration of armor by firing against homogeneous armor plate at predetermined degrees of obliquity and ranges up to 2000 yards.
- B. The T153-ST15 and T1.53-ST17 be considered the designs producing the greatest armor penetration (by static firing) of those tested.
- C. If recommendation A is not considered feasible, the following course of action is suggested:

- 1. Design T153-ST15 and T153-ST17 be fabricated and tested dynamically against the T153-ST19 (reference round) for flight and penetration characteristics at suitable ranges varying between 0 and 2000 yards.
- 2. If tests prove designs T153-ST15 and T153-ST17 to be significantly better than the reference rounds, it is recommended that consideration be given to adopting the shell which is cheapest to manufacture for use in the 120mm Tank, M103, system.

SUBMITTED:

Project Engineer

J. G. NELSON Pvt, Ord Corps Proof Director

REVIEWED:

1/B. Anderson Chief, Artillery Ammunition Branch

M.D. Kaplan G. H. A. BECHTOL

Artillery Division

APPROVED :

H. A. NOBLE

Assistant to the Deputy Director

for Engineering Testing

Development and Proof Services

REFERENCES

Test Program Request No. FA-MUR-459 Frankford Arsenal, Philadelphia 37, Pa.

Experimental Data Cards

OBSERVERS

Pvt. J. Halloran - Frankford Arsenal

Mr. Kupermann - Picatinny Arsenal

Mr. Simpson - Code B

APPENDICES

				Page No.
APPENDIX	A	_	Correspondence	A-1
APPENDIX	В	-	Round-by-Round Date	B-1
APPENDIX	С	ÇILI	Experimental Ammunition Data Cards	G-1
A PPRNITY	ח	oma	Distribution	D-7

GRIBBLICE CORPS

APPENDIX A

FRANKFORD ARSEMAL Pvt JHalloran/hom/22146

IN REPLY

Philadelphia 37 Pennsylvania

ORDBG C) 471/50 1957

14 FEB 1957

REFER TO ORDEA-MUR

SUBJECT: 120mm T153 HEAT Round

TO:

Commanding General Aberdeen Proving Ground Maryland

ATTENTION: D&PS

- 1. Inclosed is Test Program Request #FA-MOR-459 outlining a program for static tests of 120mm T153 HEAT round.
- 2. It is requested that this Arsenal be notified in advance of the firing of these tests in order that representatives may be present.
- 3. Cost of tests should be applicable to RAD on Project TAl-1602

FOR THE COMMANDER:

/8/

1 Incl

1. TPR #FA-MDR-459 (in dup)

V. W. WALTERS Assistant

cc: OCO-ORDIN, w/incl
ORDEB, Mr. Kupermann w/incl Code A, Mr. Simpson w/incl

MD-90

REGRADED UNCLASSIFIED WHEN SEPARATED FROM INCLOSURES

A-1

Test Program Request #FA-MIR-459 Frankford Arsenal, Phila.37, Fa.

Pvt Halloran/hcm/5156 29 January 1957

1. Material for Test:

Item	Quantity	Component	Dwg. No.	Rev. Remarks
1	5	T153-ST19	WB3720X	Tl53E8w/o spike
2	5	T153-6T20	WB3720X	T153E8 w/o tapered wire w/spike
3	5	T153-6T14	WBSX1342	Large diameter spike cemented joints
4	5	T153-8T1 6	WBSK1342	Medium diameter spike cemented joints
5	5	T153-6T15	WBSK1342	Same as ST16 except wire passes through cone near apex
6	5	T153-6T17	WBSK1342	Same as ST16 but with "snap-in"
7	5	T153-6T18	WBSK1342	Spike closed at nose end, all wire connections made at base of shell

2. Project Authority:

- (a) Project No. TA1-1602
- (b) PESD No. 70405530-01-10902
- 3. Arsenal Expenditure Order No.

64734-03

4. Object of Development:

To develop a 120mm HEAT round for the T123 gun.

5. History Sketch:

The development of this shell was initiated in 1950 with the technical supervision assigned to Picatinny Arsenal and the development contract awarded to Code A. The program was suspended in January 1956 at 80% completion and then reinstated in August 1956 with a target completion date of June 1957. Since the reinstatement of the project, Frankford Arsenal has been given the technical supervision and at this date the negotiations of a contract with Code A to complete the subject development have just been completed.

REGRADING DATA CANNOT BE FREDETERMINED

Test Program Request #FA-MDR-459 Frankford Arsenal, Phila.37, Pa.

The requirements of this round are to defeat 16" of armor with maximum behind-the-plate effect at a range of 2000 yards with a probable error of .2 mils vertical and horizontal. At the present time the problem areas are thought to be as follows:

(1) The wiring system is inadequate

(2) The fusing may be inadequate

(3) The lucky mounting system is inadequate

(4) The space in the spike to permit jet formation is inadequate

The accuracy of this round is satisfactory and the development program now being undertaken will be an attempt to improve the terminal ballistics and round dependability without impairing accuracy. This static test is the first under the present program and will be fired in an attempt to determine the optimum spike configuration for penetration.

6. Description of Changes Made Since Last Proving Ground Test:

Items 1 and 2 of section (1) of this request are the present T153E8

Design with and without the spike attached, both being without the tapered wire and lucky assembly of the complete round.

Item 3, the T153-ST14, is the same shell with a tapered spike of much larger diameter than the standard and with a camented joint between the body and spike and between the locking ring and body replacing the present threaded joints. This design also includes a packed lucky with the wire being carried in a flexible conduit through the explosive charge.

Item 4, T153-ST16, is the same as ST14 except that the spike is of an intermediate diameter between ST14 and the present E8 spike.

Item 5, T153-ST15, is the same as ST16 except that the wire passes through the cone and explosive charge close to the longitudinal axis of the shell.

Item 6, T153-ST17, is the same as ST16 except that it is equipped with a "snap-in" cone which is seated on the spike rather than in the body.

Item 7, T153-ST18, has a spike which is closed at the nose and a wiring system in which all wire connections are made at the base of the shell.

7. Local Tests:

None

8. Object of Test:

To determine the static penetration of the standard T153E8 round with and without the spike and of the five new designs.

REGRADING DATA CANNOT BE PREDETERMINED

-2-

Test Program Request #FA-MDR-459 Frankford Arsenal, Phila 37, Pa

9. Precautions in Handling and Testing:

Normal handling of live loaded rounds for static firings.

10. Recommended Test Program:

Fire all static devices in a vertical position against approximately twenty-eight inches of stacked homo-armor plate. The top five plates shall be at least 8"x 8" square to provide a suitable jet entry area, and the remaining plates shall be 6"x 6" minimum. The following data should be recorded:

- (a) Total penetration
 (b) Size of entrance and exit hole at each plate
 (c) Any unusual hole pattern

The shell as received will be comp B loaded with a formed base element cavity, for functioning of the shell, the system shown in PX-13-1317, previously furnished the proving ground, should be used as a guide. Corps of engineers special electric blasting caps should be used for this test.

This test may be altered at the discretion of the proof officer, with the consent of the Project Engineer.

11. Coordinations

- (a) Chief of Ordnance (ORDTA)
- (b) Picatinny Arsenal
- (c) Aberdeen Proving Ground
- (d) Code A
- (a) Frankford Arsenal

-3-

REGRADING DATA CANNOT BE PREDETERMINED

ROUND-BY-ROUND DATA

APPENDIX B

STATIC TESTS OF 120MM T153 HEAT SHELL

All Plate Measurements Given are in Inches

Each Plate is 1-1/32" Thick

PLATE NO.		ASUREMENTS r - Inches	OBSERVATIONS
	Entrance	Exit	
		T153 - ST14-1	
1 2 3 4 5 6 7 8 9	2-1/4 x 2-1/8 1-9/16 x 1-9/16 1-5/16 x 1-1/4 1-1/4 x 1-3/16 1-1/8 x 1 1-1/8 x 1-1/16 7/8 x 7/8 3/4 x 11/16 5/8 x 5/8 5/8 x 9/16	1-7/8 x 1-7/8 1-5/16 x 1-5/16 1-1/8 x 1-1/16 1-1/8 x 1-1/8 1-3/16 x 1-1/8 15/16 x 7/8 13/16 x 3/4 3/4 x 11/16 9/16 x 1/2 9/16 x 9/16	Indentation on entrance side of No.1 - 4-1/2 x 3-9/16 x 5/16" deep.circumferential to hole. Jet in No.5 - 2-1/2" — entrance; 2-1/4" — exit.
11 12 13 14 15 16 17 18 19 20 21	1/2 x 1/2- 7/16 x 7/16 1/2 x 7/16 3/8 x 3/8 7/16 x 7/16 3/8 x 5/16 7/16 x 7/16 7/16 x 3/8- 1/2 x 7/16 7/16 x 3/8	9/16 x 1/2 5/8 x 9/16 9/16 x 1/2 7/16 x 3/8 3/8 x 5/16 1/2 x 7/16 7/16 x 3/8 9/16 x 1/2 7/16 x 3/8 13/16 x 3/4	Jet in No.13 - 1"exit. Cu trace on entrance of
	T	153 - ST14-2	No. 21.
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	2-5/16 x 2-1/4 1-3/4 x 1-3/4 1-7/16 x 1-7/16 1-3/8 x 1-5/16 1-3/16 x 1-1/8- 1-1/4 x 1-3/16 15/16 x 7/8 3/4 x 3/4 11/16 x 5/8- 5/8 x 9/16 9/16 x 1/2 9/16 x 7/16 1/2 x 7/16 7/16 x 5/16 7/16 x 3/8	2-1/4 x 2-1/8 1-9/16 x 1-1/2 1-5/16 x 1-1/4- 1-1/4 x 1-3/16 1-1/4 x 1-3/16 1-1/8 x 1 - 3/4 x 11/16 11/16 x 9/16 11/16 x 5/8 5/8 x 5/8 9/16 x 1/2 1/2 x 1/2 7/16 x 3/8 9/16 x 1/2 7/16 x 3/8 7/16 x 3/8	Indentation on edge of hole 3/4"x 1-3/4"x 7/16 deep on entrance of No. 1. Jet in No.6 - 3-3/16" 1 entrance; 1-5/8 1 exit.

PIATE NO.	HOLE MEAS		CBSERVA TIONS
	Entrance	Exit	
17 18 19 20	7/16 x 3/8 7/16 x 5/16 5/8 x 9/16	7/16 x 3/8 9/16 x 1/2 13/16 x 3/4	Cu trace on No. 20.
	T153 -	ST14-3	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	2 x 2 1-5/8 x 1-1/2 1-7/16x 1-5/16 1-1/4 x 1-1/4 1-1/8 x 1-1/16 1 x 15/16 13/16 x 11/16 11/16 x 11/16 9/16 x 1/2 9/16 x 9/16 9/16 x 1/2 1/2 x 1/2 1/2 x 7/16 1/2 x 7/16 1/2 x 7/16 1/2 x 7/16	2 x 1-3/4- 1-3/8 x 1-5/16 1-3/4 x 1-1/4- 1-1/8 x 1-1/16 1 x 1 15/16 x 7/8- 7/8 x 13/16 3/4 x 11/16 5/8 x 5/8 5/8- x 5/8- 9/16 x 9/16 1/2 x 7/16 1/2- x 7/16 7/16 x 3/8 9/16 x 3/8	5/8"x 1"x 1/2 deep on ent. of No. 1.
17 18	1/2 x 5/16 11/16 x 9/16 T153 - ST	3/4 x 5/8	
1 2 3 4 5 6 7 8	2-1/8 x 2 2 x 1-7/8 1-3/4 x 1-3/4 1-1/8 x 1-1/16 15/16 x 3/4 7/8 x 3/4 13/16 x 9/16 5/16 x 1/2	1-7/8 x 1-3/4 1-7/8 x 1-3/4 1-3/8 x 1-1/8 1 x 5/8 7/8 x 3/4 7/16 x 5/8- 3/4 x 11/16	Indentation circumferential to hole ent. No. 1 3-3/8"x 3-1/2"x 5/16" deep. Jet in No.5 - 2-1/2" ent.; 2" exit. Hole in No. 8 - 7/8" deep.
1 2 3 4 5 6 7 8	T153 - 5 2-1/4 x 2-1/4 1-1/2-x 1-5/16 1-5/16x 1-1/4 1-1/4 x 1-1/8 7/8 x 7/8 13/16 x 3/4 5/8 x 5/8- 5/8 x 7/16	1=7/8 x 1=1/2 1=1/4 x 1=1/4- 1=1/4-x 1=3/16 1=3/16x 1=1/8 7/8 x 7/8 3/4 x 3/4- 5/8 x 7/16 11/16 x 5/8	Indentation circumferential to hole ent. No. 1 - 2-3/4"x 2-3/4"x1/4" deep. Jet in No. 4 - 2-1/4" ent.; 3-1/4 exit.

PLATE NO.	HOLE MEAS		OBSERVATIONS
	Entrance	Exit	
9 10 11 12 13	9/16 x 1/2 1/2 x 1/2 1/2 x 7/16 1/2 x 1/2 1/2 x 1/2	9/16 x 1/2 1/2 x 1/8 9/16 x 9/16 9/16 x 1/2 7/16 x 3/8	Jet in No. 33 - 1-3/8™ ⊥ ent.
14 15 16 17 18 19 20	7/16 x 3/8 3/8 x 3/8 3/8 x 3/8 1/2 x 7/16 7/16 x 7/16 9/16 x 7/16 1/2 x 5/16	1/2 x 1/2 7/16 x 7/16 7/16 x 1/2 7/16 x 7/16 9/16 x 1/2 1/2 x 1/2	Hole in No. 20 - 1/4 deep.
	T153	- ST15-1	
1 2 3 4 5 6	1-3/16x 1-1/8 1-1/8 x 1-1/8 1-3/16x 1-1/16	1-1/8 x 1-1/8 1-1/16 x 1-1/16 7/8 x 3/4	3-1/2 ^m x 3-3/4 ^m x 7/16 ^m deep.
5 6 7 8 9 10 11 12	7/8 x 13/16 3/4 x 5/8 5/8 x 9/16 5/8 x 5/8 9/16 x 1/2 9/16 x 9/16	3/4 x 11/16 11/16 x 5/8 5/8 x 9/16 9/16 x 9/16 9/16 x 9/16 5/8 x 9/16	Jet in No.16 - 3/4" ent.; 1" exit.
13 14 15 16 17 18 19 20	5/8 x 9/16 9/16 x 1/2 1/2 x 7/16 1/2 x 7/16 3/8 x 3/8 5/16 x 5/16 7/16 x 7/16 11/16 x 1/2	9/16 x 9/16 9/16 x 1/2 1/2 x 1/2 9/16 x 9/16 3/8 x 5/16 1/2 x 1/2 1/2 x 1/2	Hole in No.20 - 5/8 deep. Slight bulge on exit of No. 20.
20		ST15-2	
1 2 3 4	1-1/2x 1-3/8 1-1/2x 1-7/16 1-1/8x 1-1/8	2 x 1-1/2 1-7/16 x 1-1/4 1-1/4 x 1-1/4 1-1/8 x 1-1/8	Spike still in No. 1. Spike extended 3/4" exit No. 1.
3 4 5 6 7 8	1-1/8x 1 1-1/4 x 1-1/8 3/4 x 3/4 11/16 x 11/16	1-1/8 x 1-1/16 7/8 x 11/16 3/4 x 3/4 11/16 x 11/16	Jet in No.6 - 3-3/8" 1 ent.; 2-1/4 1 exit.
9	5/8 x 5/8 9/16 x 9/16	5/8 x 9/16 9/16 x 9/16	Jet in No.16 - 3/8" ent.; l" exit.

PLATE	NO.	House MAS		OBSERVATIONS
		Entrance	Rxit	
11 12 13 14 15 16 17 18 19 20		9/16 x 9/16 9/16 x 9/16 9/16 x 1/2 9/16 x 1/2 1/2 x 7/16 3/8 x 3/8 7/16 x 3/8 7/16 x 3/8 9/16 x 1/2 1/2 x 1/2	5/8 x 9/16 9/16 x 1/2 9/16 x 9/16 1/2 x 1/2 7/16 x 7/16 3/8 x 3/8 7/16 x 3/8 1/2 x 7/16 9/16 x 1/2	Hole in No. 20 - 1/16 deep
		T153	3 - ST15-3	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18		2-3/16 x 2-1/8 1-1/4 x 1-1/8 1-5/16 x 1-1/8 1-1/4 x 1-1/4 1-5/16 x 1-1/4 3/4 x 11/16 5/8 x 9/16 11/16 x 5/8 9/16 x 1/2 1/2 x 1/2 7/16 x 3/8 1/2 x 1/2 7/16 x 7/16 1/2 x 7/16 1/2 x 7/16 9/16 x 3/8 9/16 x 3/8 9/16 x 3/8	1-1/2 x 1-3/16 1-3/8 x 1-3/8 1-1/4 x 1-3/16 1-3/16 x 1-3/16 7/8 x 3/4 11/16 x 5/8 5/8 x 9/16 5/8 x 9/16 9/16 x 9/16 9/16 x 1/2 9/16 x 9/16 1/2 x 1/2 1/2 x 9/16	ent.; 2-3/4 exit. Jet in No.15 - 3/4" ent.; 1/2" exit.
1 2 3 4 5 6 7 8 9 10 11 12 13 14		T153 2=1/4 x 2=1/8 1=1/4 x 1=1/2 1=1/4 x 1=1/4 1=1/4 x 1=3/16 1=1/8 x 1=1/8 1 x 7/8 3/4 x 3/4 5/8 x 5/8 9/16 x 9/16 1/2 x 1/2 1/2 x 7/16 1/2 x 1/2 1/2 x 7/16 9/16 x 1/2	1-7/8 x 1-3/4 1-5/16 x 1-3/16 1-1/4 x 1-1/4 1-3/16 x 1-1/8 1 x 15/16 7/8 x 3/4 3/4 x 11/16 3/8 x 9/16 9/16 x 9/16 9/16 x 1/2 1/2 x 1/2 1/2 x 7/16 9/16 x 7/16 1/2 x 7/16	Jet in No.5 - 2-1/2" ent.; 4" exit. Jet in No.16 - 1/4" ent.; 5/8" exit. Hole in No.20 - 1" deep. Bulge on No.20 exit.

PIATE NO.	HOLE MEAST		CESTRVATIONS
	Entrance	Brit	
15	7/16 x 7/16	9/16 x 1/2	
16	$1/2 \times 7/16$	$3/8 \times 3/8$	
17	$3/8 \times 3/8$	1/2 = 5/16	0
18	$7/16 \times 3/8$	$7/16 \times 3/8$	
19 20	1/2 x 7/16 5/8 x 1/2	3/4 x 1/2	
	n	53 - ST15-5	and the second
1		1-7/8 = 1-3/4	Spike still in No. 1.
2	1-3/4 = 1-3/4	$1-1/4 \times 1-3/16$	Spike extends 1-13/16" _
3	1-1/4 x 1-5/16	$1-1/4 \times 1-3/16$	exit No. 1.
1 2 3 4 5 6 7 8 9	1-3/16 ± 1-1/8 1-3/16 ± 1-1/8	1-1/8 x 1-1/8 1-3/16 x 1-1/8	Jet in No.6 - 3-1/2" ent.; 2-3/4" exit.
6	1-1/8 x 1-1/8	1 x 15/16	one.; 2-3/4-1 exte.
7	$13/16 \times 3/4$	3/4 x 11/16	
8	3/4 = 3/4	11/16 x 5/8	Jet in No.11 - 1/8"
9	11/16 x 5/8	$9/16 \times 9/16$	ent.
10	$9/16 \times 9/16$	9/16 = 9/16	
11	$9/16 \times 1/2$	$9/16 \times 9/16$	Jet in No.15 - 7/8"
12	1/2 = 7/16	5/8 = 5/8	exit.
13	9/16 x 1/2	1/2 = 7/16	# Aug W. 00
14	$1/2 \times 7/16$	1/2 = 7/16	Cu trace on No.20 ent.
15 16	9/16 x 1/2 3/8 x 3/8	9/16 x 1/2- 3/8 x 5/16	
17	3/8 = 5/16	7/16 x 5/16	
18	$7/16 \times 3/8$	1/2 x 7/16	* *
19	9/16 x 1/2	$1/2 \times 3/8$	
20	าาร	3 - ST16-1	
			To do make ad on and manufacture and a 2
1	2-1/4 x 2-1/8 1-1/2 x 1-3/8	2 x 1-3/4 1-5/16x 1-3/8	Indentation circumferential to ent.hole No.1 -
3	1-1/4 x 1-1/4	1-1/4x 1-3/16	3-9/16"x 2-7/6"x 5/16"
4	$1-1/4 \times 1-1/8$	1 x 1	deep.
5	1 x 1	1 = 15/16	Jet in No.5 - 3" ent.3
6	1 x 7/8	13/16 x 11/16	2-5/8" exit.
7	3/4 x 11/16	11/16 x 5/8	
8	5/8 = 5/8	$9/16 \times 9/16$	Jet in Ho.14 - 3/8
1 2 3 4 5 6 7 8 9	$9/16 \times 1/2$	$1/2 \times 1/2$	ent.
10	$\frac{1}{2} \times \frac{1}{2}$	$1/2 \times 1/2$	
13 14	1/2 x 7/16	5/8 x 9/16	Jet in No.18 - 7/8 1
13	9/16 x 3/8 1/2 x 7/16	$1/2 \times 7/16$	ent.; 5/8 deep in plate.
14	9/16 = 3/8	7/16 x 7/16 1/2 x 7/16	V
15	1/2 = 7/16	7/16 x 7/16	Slight bulge on exit
15 16	7/16 x 7/16	$7/16 \times 3/8$	No. 18

B-5

PIATE NO.		SUR MENTS - Inches	OBSERVATIONS
4	Entrance	Brit	
17 18	1/2 x 7/16 11/16 x 9/16	9/16 x 1/2	
		T153 - ST16-2	
1 2 3	1-3/4 x 1-1/4 1-3/8 x 1-5/16 1-3/16 x 1-1/16	1-1/4 x 1-1/4- 1-3/16 x 1-3/16 1-3/16 x 1-1/8	Spike broke up in hole No.1
123456789	1-1/8 x 1-1/8 1 x 7/8 3/4 x 5/8	1 x 1 3/4 x 11/16 3/4 x 3/4	Jet in No.4 - 2-1/2" ent.; 4-3/4" exit.
7 8	11/16 x 11/16 1/2 x 1/2- 5/8 x 9/16	9/16 x 1/2 1/2 x 3/8 5/8 x 9/16	Hole in No.16 - 5/16" deep.
10 11 12	9/16 x 9/16 9/16 x 1/2 13/16 x 1/2	9/16 x 1/2 11/16 x 1/2 1/2 x 1/2	
13 14	$1/2 \times 7/16$ $7/16 \times 3/8$	1/2 x 7/16 9/16 x 1/2-	
15 16	1/2 x7/16 9/16 x9/16	9/16 x 5/16	
		T153- ST16-3	
1 2 3 4	1-3/4x 1-5/8 1-5/16 x 1-3/16	1-5/16 x 1-3/16 1-5/16 x 1-1/4	Spike left in No.1 hole. Pieces of Cu left in spike.
5	1-3/8 x 1-3/8 1-1/4 x 1-1/8 1-1/8 x 1 1 x 15/16	1-3/16 x 1-3/16 1-1/8x 1-1/16 1 x 7/8 13/16 x 3/4	Jet in No.6 - 3-1/4" ent.; 2-1/4" exit.
6 7 8 9	13/16 x 11/16 11/16 x 5/8 5/8 x 9/16	11/16 x 5/8 5/8 x 9/16 5/8 x 9/16	Jet in No.16 - 9/16" ent.; 3/4" exit.
11 12 13	9/16 x 1/2 1/2 x 1/2 9/16 x 1/2	9/16 x 1/2 9/16 x 1/2 9/16 x 1/2	Piece of Cu 1-3/8"x 1-3/4" x 1/4 thk.on exit No.18
14 15 16	1/2 x 1/2 1/2 x 3/8 7/16 x 3/8	1/2 x 1/2 1/2 x 1/2 9/16 x 9/16	Hole No.19 - 7/16" deep.
17 18 19	9/16 x 1/2 7/16 x 7/16 1-1/16 x 1	$3/8 \times 3/8$ $3/4 \times 11/16$	

PIATE NO.	Control of the contro	EASUREMENTS or - Inches	CBSERVA TIONS
	Entrance	Exit	
	11	T153 - ST16-4	
1 2 3	1-1/2 x 1-7/16 1-1/4 x 1-1/8	2 x 1-3/4 1-1/4 x 1-1/4 1-1/4 x 1-3/16	Jet in No.1 - 1-13/16" ent.
1 2 3 4 5 6 7 8	1-3/16 x 1-1/8 1-1/8 x 1-1/16 7/8 x 13/16	1-3/16 x 1-1/16 7/8 x 7/8 7/8 x 13/16	Jet in No.4 - 3-1/8" ent.; 2-1/8" exit.
7 8	15/16 x 7/8 11/16 x 5/8	11/16 x 11/16 5/8 x 5/8	Hole in No.17 - 11/16"deep
9 10 11	5/8 x 5/8 5/8 x 9/16 5/8 x 9/16	5/8 x 9/16 11/16 x 5/8 9/16 x 9/16	Bulge on exit No. 17.
12 13 14	9/16 x 1/2 1/2 x 1/2 7/16 x 3/8	5/8 x 5/8- 7/16 x 7/16 7/16 x 3/8-	
15 16 17	7/16 x 7/16 7/16 x 7/16 7/16 x 7/16	9/16 x 5/16 9/16 x 1/2	
	_ <u></u>	153 - ST16-5	
1 2 3 4	1-3/4 x 1-9/16 1-5/8 x 1-1/2- 1-5/16 x 1-3/16 1-5/16 x 1-3/16	1-7/8 x 1-1/2 2 x 1-7/8- 1-1/4 x 1-3/16 1-1/8 x 1-1/8	Jet in No.6 - 9-1/4" ent.; 1-13/16" exit.
567	1-1/4 x 1 1-1/8 x 1-1/16 1 x 1	1-1/16 x 1 1-1/16 x 1 7/8 x 3/4	Jet in No.13 - 5/16" ent.
8 9 10	13/16 x 3/4 11/16 x 5/8- 5/8 x 9/16	11/16 x 5/8 11/16 x 1/2 9/16 x 1/2-	Jet in No.14 - 7/8" exit.
11 12 13	1/2 x 1/2- 5/8 x 9/16 9/16 x 9/16	9/16 x 9/16 5/8 x 5/8 1/2 x 1/2	Hole in No.18 - 15/16" deep.
14 15 16	7/16 x 1/2 9/16 x 1/2 1/2 = 7/16	1/2 x 1/2 9/16 x 1/2- 5/8 x 9/16	Bulge on excit No. 18.
17 18	9/16 x 1/2 3/4 x 5/8	$3/8 \times 3/8$	
	<u>T1</u>	.53 = ST1 7-1	
2	1-3/4 x 1-5/8	$1-1/2 \times 1-1/2$	Spike left in No.1
1 2 3 4 5	1-3/4 x 1-3/8 1-1/4 x 1-1/4 1-3/16 x 1-1/8	1-5/8 x 1-3/8 1-1/4 x 1-3/16 1-1/16 x 1	Jet in No.6 - 3-3/4" i ent.; 2" i exit.

PLATE NO		EASUREMENTS or - Inches	CESERVA TIONS
	Entrance	Edt	
6	1-1/8 x 1 7/8 x 13/16	7/8 x 13/16 3/4 x 5/8-	Jet in No.10 - 7/16"
8 9 10 11	3/4 x 5/8 5/8 x 5/8 5/8 x 1/2 5/8 x 9/16	5/8 x 9/16 9/16 x 9/16 11/16 x 9/16 9/16 x 1/2	Jet in No.12 - 9/16" ent.
12 13 14	9/16 x 1/2 1/2 x 1/2 7/16 . 7/16	1/2 x 1/2 1/2 x 1/2 9/16 x 1/2-	Cu Trace on ent. No. 20.
15 16 17 18	1/2 x 3/8 3/8 x 3/8 7/16 x 3/8 7/16 x 3/8	1/2 x 7/16 9/16 x 7/16 7/16 x 3/8- 5/8 x 7/16	Ф
19 20	5/8 x 1/2	7/16 x 3/8	
		T153 - ST17-2	d ²
2 3	1-15/16 x 1-3/4 1-3/4 x 1-1/4 1-3/16 x 1-1/8	2-1/2 x 2-3/8 1-1/2 x 1-1/8 1-1/8 x 1-1/8-	Jet in No.5 - 1-3/4" 1 ent.; 4" 1 exit.
4 5 6 7	1-1/8 x 1 1-1/16 x 1-1/16 15/16 x 13/16 3/4 x 5/8	1-1/8 x 1-1/16 1 x 15/16 7/8 x 13/16 7/8 x 13/16	Jet in No.11 - 5/16" ent.
8 9 10	11/16 x 11/16 5/8 x 5/8 9/16 x 1/2	11/16 x 5/8 5/8 x 5/8 9/16 x 9/16	
11 12 13	9/16 x 1/2- 7/16 x 7/16 7/16 x 3/8	9/16 x 1/2 7/16 x 7/16 7/16 x 9/16 3/8 x 5/16	
14 15 16 17	7/16 x 3/8 7/16 x 3/8 3/8 x 3/8- 1/2 x 7/16	3/8 x 3/8 3/8 x 3/8 9/16 x 1/2	
18 19	7/16 x 7/16 15/16 x 7/8	13/16 x 3/4	
2		T153 - ST17-3	
1	2.2// 2.1/2	1-3/8 x 1-3/16	Spike left in No. 1.
1 2 3 4 5 6	2-3/4x 1-1/2 1-5/8 x 1-1/4 1-3/16 x 1-3/16 1-1/8 x 1-1/16	1-1/8 x 1-1/16 1-3/16 x 1-1/16 1-1/16 x 1	Jet in No.6 - 2-11/16" ent.; 3-1/8 exit.
6 / 8	1-1/16 x 1 15/16 x 7/8 1-1/16 x 7/8	15/16 x 15/16 7/8 x 13/16 1 x 3/4	Jet in No.20 - 1-1/4" 1 ent.
		B-8 CONFIDENTIAL	

PIATE NO.		ASUREMENTS or - Inches	OBSERVATIONS
	Entrance	Exit	
9	3/4 x 5/8	5/8 x 1/2	
10	$5/8 \times 1/2$	5/8 x 5/8	
11	5/8 x 1/2	$5/8 \times 9/16$	Φ.
12	$5/8 \times 9/16$	5/8 x 5/8	
13	$5/8 \times 5/8$	$9/16 \times 1/2$	
14	$9/16 \times 1/2$	$5/8 \times 9/16$	
15	$1/2 \times 1/2$	$1/2 \times 7/16$	
16	7/16 x 7/16	$9/16 \times 1/2$	
17	$9/16 \times 1/2$	$9/16 \times 5/16$	
18	$1/2 \times 7/16$	$5/8 \times 1/2$	
19	$5/8 \times 7/16$	$5/8 \times 9/16$	
20	$3/4 \times 5/8$		*
		153 - ST17-4	
1			
1 2 3 4	$1-3/4 \times 1-3/8$	$1-3/4 \times 1-3/8$	Spike left in No.1.
3	$1-3/8 \times 1-1/4$	1-3/8 x 1-1/4-	
Ž.	1-3/16 x 1-1/8	1-1/16 x 1-1/16	Jet in No.5 - 1-3/4"
5	$1-1/8 \times 1-1/16$	$15/16 \times 7/8$	ent.; 2-3/4" exit.
6	7/8 x 13/16	$7/8 \times 3/4$	5.101, 12 J/1 2 5.2201
5 6 7 8 9	3/4 x 11/16	$3/8 \times 3/8$	Cu trace on ent. No.17.
Ŕ	11/16 x 3/8	$11/16 \times 3/8$	
o o	$\frac{5/8 \times 1/2}{5}$	5/8 x 1/2	
10	$9/16 \times 1/2$	$3/8 \times 9/16$	
11	$1/2 \times 1/2$	$7/16 \times 3/8$	
12	$9/16 \times 1/2$	$5/8 \times 1/2$	
13	$1/2 \times 3/8$	$5/8 \times 7/16$	J
14	9/16 x 1/2	$1/2 \times 7/16$	
	$1/2 \times 1/2$	$\frac{1}{2}$ x $\frac{1}{2}$	
15		5/16 x 7/16	
16 17	$3/4 \times 3/4$	5/10 x //10	
•	T1	53 - ST17-5_	
7			
1 2 3 4 5 6 7 8 9	$1-5/8 \times 1-3/8$	1-1/16 x 1-1/16	Spike left in No. 1.
3	$1-1/8 \times 1-1/8$	$1-1/8 \times 1-1/16$	_
4	$1-1/8 \times 1-1/8$	$1-3/16 \times 1-1/16$	Jet in No.6 - 2-7/8"
5	$1-3/16 \times 1-1/8$	$1-1/8 \times 1-1/8$	ent.; 2-3/4" \(\) exit.
6	$1-1/8 \times 1$	lxl	•
7	$7/8 \times 7/8$	$13/16 \times 3/4$	Hole in ent.No.21 -
8	3/4 = 3/4	$5/8 \times 1/2$	1/2" deep.
9	5/8 = 5/8	$9/16 \times 9/16$	
10	$9/16 \times 9/16$	$9/16 \times 9/16$	
11 12	5/8 x 1/2	$5/8 \times 9/16$	
3.0	$9/16 \times 9/16$	$1/2 \times 1/2$	

B-9

PIATE NO.		EASUREMENTS er - Inches	OBSERVACIONS
	Entrance	Brit	
13 14 15 16 17 18 19 20 21	1/2 x 1/2 1/2 x 7/16 3/8 x 3/8 7/16 x 7/16 7/16 x 1/2 3/8 x 3/8 3/8 x 5/16 1/2 x 3/8 5/8 x 5/16	1/2 x 1/2 9/16 x 1/2 5/8 x 5/8 1/2 x 1/2 3/8 x 5/16 3/8 x 5/16 1/2 x 3/8 5/8 x 5/8	
		T153 - ST18-1	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	1-3/4 x 1-5/8 1-9/16 x 1-1/2 1-7/16 x 1-1/8 1-1/4 x 1-1/4- 1-1/8 x 1-1/16 1-3/16 x 1-1/8 3/4 x 3/4- 1/2 x 7/16 5/8 x 5/8 9/16 x 1/2- 7/16 x 7/16 1/2 x 7/16 9/16 x 1/2- 1/2 x 7/16 7/16 x 7/16 1/2 x 7/16 7/16 x 7/16	2-3/8 x 2-1/8- 1-1/2 x 1-7/16 1-3/8 x 1-5/16 1-9/16 x 1-1/2- 1-1/8 x 1-1/16 1-1/4 x 1 5/8 x 1/2 9/16 x 1/2 5/8 x 1/2 9/16 x 9/16 9/16 x 9/16 9/16 x 7/16 9/16 x 1/2 5/8 x 7/16 1/2 x 7/16 5/8 x 9/16 9/16 x 9/16	Jet in No.6 - 3-1/2 ^N dent.; 1-7/8 dent. Cu pile-up between No.7 and No.8; No.8 and No.9; No. 9 and No. 10. Cu Trace on ent.No.19.
	p	T153 - ST18-2	
1 2 3 4 5 6 7 8 9	2-1/4 x 2-1/4 1-3/4 x 1-9/16 1-1/8 x 1-1/8- 1-1/8 x 1-1/16	1-7/8 x 1-1/2 1-3/8 x 1-5/16 1-3/16 x 1-1/8- 1-1/8 x 1-1/16	Indentation circumferential to ent.hole No.1 - 3" x 3-7/16" x 3/16" deep.
5 6 7	1-1/8 x 1 13/16 x 3/4 3/4 x 3/4-	1 x 7/8 - 7/8 x 13/16 11/16 x 11/16	Jet in No.5 - 2-1/2 " ent.; 3" exit.
8 9 10	5/8 x 9/16 9/16 x 1/2 9/16 x 1/2-	5/8 x 9/16 5/8 x 5/8 9/16 x 9/16	Jet in No.15 - 3/16" ent.; 1/2" exit.
11 12 13	9/16 x 7/16 9/15 x 1/2 1/2 x 1/2	5/8 x 9/16 1/2 x 1/2- 1/2 x 5/16	Hole No.18 - 9/16" deep.

B-10

PIATE NO.		ASUREMENTS r - Inches	OBSERVATIONS
	Entrance	Excit	•
14 15 16 17 18	1/2 x 7/16 9/16 x 9/16 1/2 x 5/16 1/2 x 1/2 1/2 x 7/16	9/16 x 7/16 9/16 x 1/2 1/2 x 5/16 5/8 x 9/16	495
Alex.	-	T153 - ST18-3	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	2-5/16 x 2-3/8 1-1/4 x 1-1/8 1-3/16 x 1-1/8 1-1/4 x 1-3/16	1-1/4 x 1-1/8 1-1/8 x 1-1/8 1-1/8 x 1-1/8 1-1/16 x 1-1/16 1-1/16 x 1-1/16 1x 1 13/16 x 3/4 - 13/16 x 13/16 11/16 x 5/8 11/16 x 5/8 11/16 x 5/8 1/2 x 1/2 1/3 x 5/8	Part of spike flange in hole No. 3. Jet in No.6 - 2-7/8" ent.; 2-9/16" exit. Jet in No.17 - 3/16" ent. Cu splash 1-3/8"x 1/2" x 1/16" deep between No.18 and No. 19.
	T1.5	3 - ST18-4	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	1-3/4 x 1-1/2 1-1/4 x 1-1/8 1-1/8 x 1-1/16 1 x 1 7/8 x 7/8 - 3/4 x 11/16 3/4 x 5/8 9/16 x 1/2- 9/16 x 7/16 1/2 x 3/8 9/16 x 1/2 1/2 x 1/2- 1/2 x 7/16 7/16 x 7/16 7/16 x 7/16 3/4 x 3/4	1-7/8 x 1-3/4 1-3/4 x 1-1/4 1-3/16 x 1-1/8 7/8 x 13/16 13/16 x 13/16 5/8 x 5/8 11/16 x 5/8- 5/8 x 9/16 9/16 x 9/16 11/16 x 1/2- 5/8 x 9/16 9/16 x 7/16 9/16 x 1/2- 1/2 x 7/16 1/2 x 7/16 1-3/16 x 7/8	Spike left in hole No. 1. Jet in No. 5 - 2-3/4"

PIATE NO.		ASUREMENTS or - Inches	OBSERVATIONS
	Entrance	Exit	
		T153 - ST18-5	
1 2 3 4 5 6 7 8 9	2-1/4 x 2-1/8 1-1/4 x 1-1/4 1-1/2 x 1-3/8 1-1/8 x 1-1/8	1-1/2 x 1-3/8 1-5/8 x 1-3/8 1-1/8 x 1-1/8 1-1/16 x 1	Indentation circumferential to No.1 ent 2-3/4" x 2-5/8"x 1/4" deep.
5	1 x 7/8 ± x 1 11/16 x 5/8	1 x 1 3/4 x 11/16 11/16 x 5/8	Jet in No.6 - 3-3/4" 4 ent.
8 9 10	5/8 x 1/2 9/16 x 1/2 9/16 x 1/2	5/8 x 9/16 9/16 x 9/16 1/2 x 1/2	Jet in No.16 - 3/4" ent.
11 12 13	9/16 x 7/16 9/16 x 1/2 9/16 x 1/2	9/16 x 9/16 9/16 x 1/2- 5/8 x 9/16	Jet in No.18 - 3/8" ent.
14 15	9/16 x 1/2 9/16 x 1/2 1/2 x 7/16	9/16 x 1/2 1/2 x 1/2	
1.6 17 18	1/2 x 1/2 5/16 x 3/8- 9/16 x 5/16	$1/2 \times 1/2 - 3/4 \times 11/16$	
		T153 - ST19-1	
1 2 3 4 5	2-1/16 x 2 1-5/16 x 1-5/16 1-1/4 x 1-1/4 1 x 1	1-13/16 x 1-9/16 1-3/8 x 1-1/4 1-1/16 x 1-1/16 1-1/8 x 1-1/8	Jet in No.4 - 2-3/8" ent.; 3" exit.
	15/16 x 7/8 13/16 x 13/16	7/8 x 13/16 3/4 x 5/8	Steel splash between No. 7 and No. 8.
6 7 8 9 10	$3/4 \times 5/8$ $13/16 \times 3/4$	5/8 x 5/8 3/4 x 11/16	Cu trace on No.19.
	5/8 x 5/8 9/16 x 1/2	5/8 x 5/8 9/16 x 1/2	
12	$9/16 \times 1/2$ $1/2 \times 1/2$	9/16 x 1/2 9/16 x 1/2	
13 14	1/2 x 7/16 9/16 x 9/16	9/16 x 9/16 9/16 x 9/16	
15 16	$9/16 \times 1/2$ $1/2 \times 1/2$	$1/2 \times 1/2$ $1/2 \times 7/16$	
17 18 19	$1/2 \times 7/16$ $1/2 \times 7/16$	1/2 x 3/8 7/16 x 7/16	

PLATE NO.		Surements - Inches	OBSERVATIONS
	Entrance	Exit	
	_	T153 - ST19-2	
1 2 3	1-7/8 x 1-1/2 1-5/16 x 1-5/16 1-1/8 x 1-1/8	1-5/8 x 1-1/2 1-3/8 x 1-1/8 1-1/8 x 1	Indentation 270° circum- ferential to hole No.1 ent 2"x 2"x 5/8"
4 5	1 x 15/16 13/16 x 13/16	1 x 15/16 15/16 x 7/8	deep.
2 3 4 5 6 7 8 9	13/16 x 3/4 3/4 x 11/16 3/4 x 11/16	7/8 x 13/16 3/4 x 3/4 13/16 x 11/16	Jet in No.1 - 3-1/8" ent.; 2-1/4" exit
9 10 11	11/16 x 5/8 11/16 x 9/16 3/4 x 9/16	3/4 x 11/16 11/16 x 9/16 11/16 x 5/8	Holes No.7 and No.8 are triangular.
12 13 14	11/16 x 11/16 3/4 x 5/8 9/16 x 1/2	3/4 x 9/16 1/2 x 1/2 3/8 x 3/8	Jet in No.13 - 1/2" exit.
15 16 17	3/8 x 1/4 5/8 x 1/2 3/8 x 3/8	$1/2 \times 7/16$ $5/8 \times 9/16$	Hole in No.17 - 5/8 ^m deep.
		3 - ST19-3	
1	1-9/16 x 1-3/8 1-1/2 x 1-3/8	2 x 1-3/4 1-1/4 x 1-1/4	Jet in No.3 - 3-1/2" 4
3	1-1/4 x 1··1/4 1 x 1	1-1/8 x 1-1/8 1-1/8 x 1-1/16	ent.; 1-3/4 \(\(\preceq\) excit.
1 2 3 4 5 6 7	7/8 x 7/8 13/16 x 3/4 3/4 x 3/4	1-1/16 x 15/16 15/16 x 7/8 7/8 x 7/8	Jet in No.13 - 1/4"
8 9 10	5/3 x 9/16 11/16 x 5/8 5/8 x 9/16	15/16 x 3/4 3/4 x 11/16 11/16 x 5/8	Cu splash between No.15 and No.16.
11 12 13	5/8 x 5/8 5/8 x 5/8 11/16 x 5/8	5/8 x 5/8 5/8 x 5/8 1/2 x 1/2	Hole in No.16 - 1/4" deep.
14 15 16	1/2 x 1/2 5/8 x 1/2 1/2 x 1/2	5/8 x 1/2 5/8 x 1/2	Nan o
	Tl	3 - ST19-4	
1 2 3	2-7/16 x 2 1-1/2 x 1-3/8 1-3/8 x 1-5/16	$1-7/8 \times 1-3/4$ $1-1/4 \times 1-3/16$ $1-1/4 \times 1-1/8$	Spike left in No. 1 hole
2 3 4 5 6 7	1-3/16 x 1-1/16 1-1/8 x 1-1/16 15/16 x 7/8	1-1/8 x 1-1/16 1 x 1 15/16 x 7/8	Jet in No.2 - 3-7/8" ent.; 2-7/16" exi
7	15/16 x 13/16 11/16 x 5/8	13/16 x 11/16 3/4 x 5/8	Cu in holes No.9 and No. 10.
		B-13	

PIATE NO.		PASUREMENTS or - Inches	OBSERVATIONS
	Entrance	Brit	
9 10 11	11/16 x 11/16 11/16 x 5/8 9/16 x 1/2	5/8 x 5/8 9/16 x 1/2 3/8 x 9/16	Jet in No.11 - 1/4ª ⊥ exit.
12 13 14	5/8 x 1/2 5/8 x 1/2 5/8 x 9/16	9/16 x 1/2 5/8 x 1/2 1/2 x 7/16	Cu splash between No.16 and No.17.
15 16 17	7/16 x 7/16 3/8 x 3/8 5/8 x 3/8	1/2 x 3/8 1/4 x 1/8	
		T153 - ST19-5	
2 3	1-5/8 x 1-5/8 1-5/16 x 1-3/16 1-1/4 x 1-3/16	1-7/16 x 1-3/8 1-1/4 x 1-1/8 1-3/16 x 1-1/16	Jet in No.5 - 2-9/16" 4 ent.; 3" 4 exit.
1 2 3 4 5 6 7 8 9	1 x 1 1 x 15/16 1 x 7/8 3/4 x 3/4	1-1/16 x 1 1 x 1-1/16 13/16 x 3/4 3/4 x 11/16	Cu in holes No.15 and No.16. Jet in No.17 - 1/4"
8 9 10 11	11/16 x 5/8 11/16 x 9/16 11/16 x 5/8 9/16 x 1/2	3/4 x 11/16 11/16 x 5/8 5/8 x 5/8 5/8 x 5/8	Hole in No.17 - 1/4" deep.
12 13 14	9/16 x 1/2 1/2 x 7/16 1/2 x 1/2	9/16 x 1/2 1/2 x 7/16 11/16 x 5/8	
15 16 17	5/8 x 9/16 9/16 x 1/2 5/8 x 5/8	5/8 x 9/16 11/16 x 5/8	
		T153 - ST20-1	
1 2 3 4 5 6 7 8 9	1-3/4 x 1-9/16 1-13/16x 1-5/8 1-1/4 x 1-1/4 1-3/8 x 1-5/16 1-3/16 x 1-1/8	1-5/8 x 1-9/16 1-3/8 x 1-3/8 1-3/8 x 1-3/8 1-1/4 x 1-1/4 1-3/8 x 1-3/8	Jet in No.6 - 2-9/16" ent.; 3-1/8" exit.
7 8 9	1-1/8 x 1 7/8 x 7/8 3/4 x 3/4 5/8 x 9/16 9/16 x 9/16	1 x 15/16 15/16 x 1 7/8 x 3/4 7/8 x 11/16 5/8 x 9/16	Hole in No.18 - 1/8" deep.
11 12 13 14 15	9/16 x 1/2 1/2 x 1/2 9/16 x 9/16 1/2 x 7/16 7/16 x 7/16	5/8 x 9/16 5/8 x 5/8 1/2 x 9/16 1/2 x 1/2 7/16 x 3/8	

B-14 CONFIDENTIAL

PIATE NO.		ASUREMENTS or - Inches	OBSERVATIONS
	Entrance	Exit	
16	3/8 = 3/8	11/16 x 1/2	
17	$5/8 \times 1/2$	1 x 7/8	
18	$13/16 \times 5/8$		
		T153 - ST20-2	
1 2 3 4 5 6 7 8 9	$2-1/4 \times 2-1/8$	$2 \times 1 - 3/4$	
2	$1-7/8 \times 1-1/2$	$2 \times 1-3/4$	Jet in No.6 - 2-1/4"
3	$1-1/2 \times 1-3/8$	$1-5/16 \times 1-1/4$	ent.; 3" \perp exit.
4	1-5/16x 1-5/16	$1-1/8 \times 1-1/8$	Jet in No.17 - 9/16" 🕹
6	$1-1/8 \times 1-1/8$	1-1/4 x 1-1/16 1-1/4 x 1	ent.
7	1-3/16 x 1-3/16 1 x 7/8	$13/16 \times 3/4$	ent.
g	13/16 x 11/16	$3/4 \times 3/4$	Hole in No.17 - 1/4"
0	$3/4 \times 3/4$	$1 \times 13/16$	deep.
10	13/16 x 9/16	$3/4 \times 3/4$	asop.
11	5/8 x 9/15	11/16 x 9/16	i p
12	5/8 x 9/16	9/16 x 9/16	
13	9/16 x 1/2	9/16 x 9/16	
14	$9/16 \times 1/2$	$9/16 \times 1/2$	
15	$1/2 \times 7/36$	$1/2 \times 1/2$	
16	$5/8 \times 1/2$	$13/16 \times 3/4$	
17	5/8 x 11/16		
	2	T153 - ST20-3	
1	3-1/4 x 2	2-1/8 x 1-7/8	Indentation on one side
2	$1-3/8 \times 1-5/16$	$1-3/8 \times 1-5/16$	of hole ent.No. 1 -
1 2 3	$1-3/16 \times 1-1/8$	1-3/16x 1-3/16	$2-1/2^{n}x 1-3/16^{n}x 1/4^{n}$
4	$1-1/8 \times 1-1/8$	1-1/16 x 1-1/16	deep.
	$1-1/8 \times 1$	1 x 1	Jet in No.5 - 2-7/16" _
6	7/8 = 7/8	$13/16 \times 13/16$	ent.; 3-5/16" L exit
5 6 7 8 9	$3/4 \times 11/16$	$13/16 \times 5/8$	
8	$5/8 \times 5/8$	$11/16 \times 5/8$	Jet in No.21 - 3/16" 1
	$5/8 \times 5/8$	$3/4 \times 11/16$	ent.
10	$5/8 \times 5/8$	$5/8 \times 9/16$	Hole in No.21 - 1/4" deep
11	9/16 x 9/16	5/8 = 5/8	
12	$1/2 \times 1/2$	$5/8 \times 9/16$	
13	$1/2 \times 7/16$	$9/16 \times 1/2$	
14	$1/2 \times 7/16$	$9/16 \times 9/16$	
15 16	7/16 x 3/8 1/2 x 7/16	$1/2 \times 7/16$ $1/2 \times 3/8$	
17	$1/2 \times 7/16$	$7/16 \times 3/8$	
18	7/16 x 5/16	$7/16 \times 3/8$	
	$7/16 \times 3/8$	3/4 = 3/8	
19			
19 20	5/8 x 7/16	1 x 1	

PIATE NO.		ASUREMENTS r - Inches	OBSERVA TIONS
	Entrance	Exit	
		T153 - ST20-4	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	2-1/8 x 1-7/8 1-3/8 x 1-3/8 1-1/4 x 1-1/4 1-1/8 x 1 1 x 1 1-1/8 x 7/8 1 x 7/8 7/8 x 11/16 7/8 x 3/4 3/4 x 3/4 5/8 x 1/2 5/8 x 9/16 1/2 x 7/16 3/8 x 7/16 7/16 x 3/8 7/16 x 3/8 7/16 x 3/8 3/8 x 1/4	1-3/4 x 1-3/4 1-1/2 x 1-1/2 1-3/8 x 1-5/16 1-1/8 x 1-1/8 1 x 15/16 1 x 1 7/8 x 3/4 3/4 x 3/4 3/4 x 3/4 5/8 x 9/16 5/8 x 9/16 1/2 x 1/2 1/2 x 1/2 1/2 x 1/2 1/2 x 3/8	Jet in No.6 - 2-1/4" ent.; 3" exit. Steel splatter 1/4" thick between No.9 and No. 10. Hole in No.18 - 1/2" deep.
		T153 - ST20-5	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	2-1/2 x 2 1-9/16 x 1-3/8 1-3/8 x 1-3/8 1-1/2 x 1-7/16 1-1/4 x 1-1/4 1-1/8 x 1-1/8 3/4 x 3/4 5/8 x 9/16 3/4 x 5/8 9/16 x 1/2 1/2 x 1/2 7/16 x 7/16 7/16 x 7/16 1/2 x 7/16 7/16 x 7/16 7/16 x 1/2	2-3/16 x 1-3/4 1-9/16 x 1-1/2 1-1/2 x 1-1/2 1-1/2 x 1-7/16 1-1/4 x 1-3/16 1 x 7/8 1 x 1 3/4 x 3/4 3/4 x 11/16 9/16 x 9/16 1/2 x 1/2 1/2 x 1/2 9/16 x 7/16 9/16 x 3/8 7/16 x 1/2 9/16 x 1/2	Indentation circumferential to ent.No.1 - 4-1/2" x 4" x 3/8" deep. Jet in No.6 - 2-7/8" ent.; 2-1/4" exit. Steel splash between No.8 and No.9. Jet in No.17 - 1/2" ent.

			CONF	IDENTIAL			APPENDIX C
4001-0 A. 00718, N.J.	EXP	ERIMENT	AL AMML	INITION D	ATA CARD		но 85575
T.P.R. NO.	KIND						AMM. LOT NO.
	Shell, 120MM	, BEAT, St	atic Test. T	153 ST-14			PA-E-25553
SPEC. NO.	1						QUANTITY IN LOT
DRG. NO. WBSK-1342	DRG. DATE OR REV.	ALLOT. ADVI	CE PROJ	ECT NO	RAD OR EPO	NO.	QUANTITY IN SHIPMENT
P. A. H. O. 3034-64	PROP. CHARGE	EXPECTED M	. V EXPE	CTED PRESSURE	ASSEMBLED BY		DATE OF ASSEMBLY May, 1957
COMPONENT	Metal Parts		Chg				
CIND	Assy		Bursting				
140	ASSY		Comp. B				
ORG. NO	unk	-	d	, .			
DATE OR REV.	unk	1.18	1 1				
. G'D BY	Budd-Wheel C	of ju	Holston	مر. ا			
ATE	1957	7-	1955				
OT 40.	ST-14		1:0L-7-1435		200	1	
REPARED BY	D. Scobl		CE	RTIFIED TO BY:	no Kna	PPO	INSPECTOR
	Ars Oper		PICATINNY /	ARSENAL 816	Inap	ectio	
HXPERTMEN	TAL AMMUNII	TON DAT	DOVER. NEW	JERSEY	LOT NO	PA -1	DIVISION E +2553

Y, P, R. NO.	KIND	120MM, HEAT,	Static Test 5	የን ፍ ሚሞሽል		AMM. LUT NO. PA-E-25554
SPEC NO.	Sherr	QUANTITY IN LOT				
DRG NO WBSK-1342	DRG. DATE OR REV.	ALLOT. ADVICE	PROJECT NO.	RAD OF	EFO NO.	QUANTITY IN SHIPMEN
P. A. X. O. 3034-64	PROP. CHARC.	EXPECTED M. V.	EXPECTED PR	ESSURE ASSEMBL		May, 1957
local inspec	dia. Puze, la tion. And	cky and wire a	semblies omi	Horningin		
1.27" \$.03" local inspec	dia. Puze, lution. AND	icky and wire a	semblies om			
1.27" # .03" local inspec	dia. Fuze, Lition. AND	Chg	sting ont			
1.27" # .03" local inspec	dia. Puze, lution. AND	Chg Bur Com	semblies om			
1.27" \$.03" local inspec	dia. Fuze, Li tion. And Metal Parts Assy unk	Chg	sting ont			
1.27" # .03" local inspec facts. COMPONENT KIND DRG NO. DRG DATE OR REV.	dia. Fuze, Li tion. And Metal Parts Assy unk	Chg Burn Com	sting ont			
1.27" # .03" local inspec Loc	dia. Fuze, Li tion. An p Metal Parts Assy unk unk	Chg Bur Com	sting p. B			
1.27" # .03" local inspec COMPONENT KIND DRG NO. DRG DATE OR REV. MFG D BY DATE	Metal Parts Assy unk unk Dudd Wheel	Chg Bur Com	sting p. B			
1.27" # .03" local inspec COMPONENT KIND DRG NO. DRG DATE OR REV. MFG D BY DATE LOT NO.	Metal Parts Assy unk unk Dudd Wheel	Chg Bur Com	sting p. B		Ju g.Z.	

EXPERIMENTAL AMMUNITION DATA CARD No. 85576 - LOT NO. PA-E-25554

T.P.R. NO.	KIND			,		NO. 85577 AMM. LOT NO. PA-E-25555
SPEC. NO.	Shell,	120 MM , HEAT	I Static Te	st T153 ST-16		QUANTITY IN LOT
MBSK-1342	DRG. DATE OR REV. 2-7-57	ALLOT. ADVI	CE PROJ	ECT NO.	RAD ON TO NO.	QUANTITY IN SHIPME
P. A. X. O. 3034-64	PROP. CHARGE	EXPECTED M.	V. EXPE	CTED PRESSURE	ASSEMBLED BY	June, 1957
	Metal Parts		Charge			
	Metal Parts		Bursting			
IND	Assy					
IND	unk	V , . f . c .	Bursting Comp. B	/,-		
IND RG. NO. RG. DATE OR REV.	unk unk	· //	Bursting Comp. B	1		
RG. NO. RG. DATE OR REV.	unk unk Budd Wheel G	v , / == 2. //.	Bursting Comp. B Holston			
OMPONENT ING. NO. ING. DATE OR REY. IFG'D BY ATE OT NO.	unk unk	o , /	Bursting Comp. B	Ç		
IND IRG. NO. IRG. DATE OR REV. IFG'D BY ATE	unk unk budd Wheel Go 1957 ST-16	2. //	Holston 1955 HOL-7-1435	Ç	w. Trevena	INSPECTOR
IND IRG. NO. RG. DATE OR REV. FG'D BY ATE DT NO.	unk unk budd Wheel Go 1957 ST-16		Holston 1955 HOL-7-1435	RTIPIED TO BY:	W. Trevena Inspection	, INSPECTOR
IND RG. NO. RG. DATE OR REV. FG'D BY ATE DT NO.	unk unk unk 1957 ST-16 D. Scoble	DIVISION	Holston 1955 HOL-7-1435	RTIPIED TO BY:		, INSPECTOR

ARMY-P.A. DOVER, M.J. ORDBB-42 7-28-56 80	, EXPE	RIMENTAL	AMMUNITION DA	TA CARD	NO. 85578		
T. P. R. NO.	KIND						
SPEC. NO.	Shell, 120	MM, HEAT Stati	c Test T153 ST-17		PA-E-25556 QUANTITY IN LOT		
DRG. NO WBSK-1342	DRG. DATE OR REV. 2-7-57	ALLOT. ADVICE	PROJECT NO.	RAD ON EPO NO.	QUANTITY IN SHIPMENT		
P. A. X. O. 3034-64	PROP. CHARGE	EXPECTED M. V.	EXPECTED PRESSURE	ASSEMBLED BY PA	May, 1957		

REMARKS: Packed: 2 Shell/saddle packed/wood box.

#70304111-19-40069-01. % rayed 100%. Puze cavity drilled to a depth of 2.24" / .03" and
1.27" / .03" dia. Puze Lucky and wive assemblies omitted. Accepted based on satisfactory
local inspection. X RHYED SHELL NO. 17-4 CONTAINS FOREIGN MATERIAL

1N SPIKE NOSE

, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Ara Oper	DIVISION		RSENAL JERSEN	Inspe	ction	DIVISION
PREPARED BY	D. Scobl		CER	TIFIED TO BY:	To Koa	00 00	, INSPECTOR
LOT NO.	ST-17		HOL-7-1435			2	
DATE	1957		1955 HOL-7-1435				
MFG'D BY	Budd Mheel	Co, /	Holston				
DRG. DATE OR REV.	unk	16	(()	(1)			
DRG. NO.	unk ~	1 0					
	Assy		Comp. B				
KIND	Parts		Bursting				
COMPONENT	Metal		Chg				

EXPERIMENTAL AMMUNITION DATA CARD NO. 85578 - 22 NO. PA-E-25556

	T					NO. 85579
T. P. R. NO	KIND	AMM LOT NO.				
	Shell, 1	PA-E-25557				
SPEC. NO.	onort, 1	, zosim, ilini	002010 103	11)) 01-10		QUANTITY IN LOT
		3				
DRG. NO. WBSK-1342	DRG. DATE OR REV.	ALLOT. ADVI	ALLOT. ADVICE PROJECT NO		RAD OR EPO NO.	QUANTITY IN SHIPMENT
P. A. X. O.	PROP. CHARGE	EXPECTED M.	V. EXPE	TED PRESSURE	ASSEMBLED BY	DATE OF ASSEMBLY
3034-64					PA	May, 1957
1.26" / .04" inspection.	-40069-01. X-1 Fuze, Lucky &	and wire as	semblies om	itted. Accep	oted based on sa	atisfactory local
1.26" \(\tau \).04". inspection.	Fuze, Lucky	and wire as	semblies om	itted. Accep	oted based on sa	atisfactory local
1.26" / .04" inspection.	Fuze, Lucky &	and wire as	Semblies om	itted. Accep	oted based on sa	atisfactory local
1.26" / .04" inspection.	AnD	and wire as	Charge Bursting	itted. Accep	oted based on sa	atisfactory local
1.26" / .04" inspection.	Fuze, Lucky &	and wire as	Semblies om	itted. Accep	eted based on sa	atisfactory local
1.26" / .04" inspection. COMPONENT KIND DRG NO.	Fuze, Lucky e	and wire as	Charge Bursting	itted. Accep	eted based on sa	atisfactory local
1.26" / .04" inspection. COMPONENT KIND DRG NO. DRG DATE OR REV.	Wetal Parts Assy unk unk Budd Wheel	and wire as	Charge Bursting	itted. Accep	eted based on sa	atisfactory local
1.26" / .04" inspection. COMPONENT KIND DRG NO. DRG DATE OR REV. MFG D SY	Wetal Parts Assy unk unk Budd Wheel	and wire as	Charge Bursting Comp. B	itted. Accep	eted based on sa	atisfactory local
1.26" / .04"	Wetal Parts Assy unk unk Budd Wheel	and wire as	Charge Bursting Comp. B	itted. Accep	eted based on sa	
1.26" / .04" inspection. COMPONENT KIND DRG NO. DRG DATE OR REV. MFG D SY DATE	Wetal Parts Assy unk unk Budd Wheel	and wire as	Charge Bursting Comp. B Holston 1955 HOL-7-1435	itted. Accep	w, Trevena	
1.26" / .04" inspection. COMPONENT KIND DRG NO. DRG DATE OR REV. MFG D SY DATE LOT NO.	Vetal Parts Assy unk unk Budd Mheel 1957 ST-18	and wire as	Charge Bursting Comp. B Holston 1955 HOL-7-1435	TIFIED TO BY:	eted based on sa	

T. P. R. NO	Shell, 120MM, HEAT, Static Test, T153 ST=19					22102	PA-E-25558	
SPEC NO.	Shell,	120MM, HEAT	, Static Tes	t, 1155 ST	-27	QUANTITY	IN LOT	
WBSK-1342	DRG. DATE OR REV. 2-7-54	ALLOT ADVICE	PROJECT	NO	HAD OF EPO NO.	VIITMAUD	IN SHIPMENS	
7 A. X. O. 3034-64	PROP CHARGE	EXPECTED M. V	EXPECTE	D PRESSURE	ASSEMBLED BY	May,	450EW6LT	
*70304111-19 and 1.27" f local inspec	/-	Lucky And	Mush assemb	lies omitte	ed. Accepted b	ased on	eatinfacto	
*70304111-19 and 1.27" # local inspec	-40069-01. X-r •03" dia. Puze tion. 1. 24 y 6 A 0 1 6 Metal	Lucky And	Yuan assemb	lies omitte	ed. Accepted b	ased on	atlafact	
*70304111-19 and 1.27" # local inspec	-40069-01. X-r •03" dia. Puze tion. 1. 24 y co A 016 Metal Parts	Lucky And	Yuan assemb	lies omitte	ed. Accepted b	ased on	atisfact	
70304111-19 and 1.27 / local inspec SP/A F COMPONENT	-40069-01. X-r .03" dia. Puze tion	Lucky And	Yuan assemb	lies omitte	ed. Accepted b	ased on	atisfact	
70304111-19 and 1.27 / local inspec S/3/A E COMPONENT CIND DRG. NO.	40069-01. X-r .03" dia. Puze tion	Lucky And	Yuan assemb	lies omitte	ed. Accepted b	ased on	atisfact	
70304111-19 and 1.27 / local inspec \$ 1 / A [COMPONENT KIND DRG. NO. DRG. DATE OR REV	40069-01. X-r .03" dia. Puze tion	Desky had	Yuan assemb	lies omitte	ed. Accepted b	ased on	atisfact	
70304111-19 and 1.27 / local inspec \$ f' / A f' COMPONENT KIND DRG. NO. DRG. DATE OF REY MFG'D BY	-40069-01. X-r .03" dia. Puze tion	Desky had	Chg Bursting Comp. B	lies omitte	ed. Accepted b	ased on	atinfacto	
70304111-19 and 1.27 / local inspec \$ / ^ / / [COMPONENT KIND DRG. NO. DRG. DATE OF REY MFG'D BY DATE	-40069-01. X-r .03" dia. Puze tion	Desky had	Chg Bursting Comp. B	lies omitte	ed. Accepted b	ased on	atisfact	
*70304111-19 and 1.27" / local inspec	Metal Parts Assy unk Budd Wheel (1957 ST-19	Desky had	Chg Bursting Comp. B Molston 1955 HOL-7-1435	lies omitte	FOREIGN M	ased on	atisfact	

EXPERIMENTAL ANDMUNITION DATA CARD NO. 85580 - LOT NO. PA-E-25558

ARNY-P.A. DOVER, N.J. ORDSD-43 7-24-56 SQ	. EXP	ERIMENTAL	AMMUNITION DA	ATA CARD	NO. 85581
T. P. R. NO.	KIND				AMM. LOT NO. PA-E-25559
PEC. NO.	Suell, I	ZOMM, REAT STAT	tic Test T153 ST-Q		QUANTITY IN LOT
DRG. NO. WBSK-1342	DRG. DATE OR REV. 2-7-57	ALLOT. ADVICE	PROJECT NO.	HAULOR EPO NO.	QUANTITY IN SHIPMENT
7. A. X. O. 303464	PROP. CHARGE	EXPECTED M. V.	EXPECTED PRESSURE	ASSEMBLED BY	DATE OF ASSEMBLY

REMARKS: Packed: 2 Shell/saddle packed/wood box.

#70304111-10-40069-01. X-rayed 100%. Fuze cavity drilled to a depth of 2.24" / .03" and 1.27" / .03" dia. Fuze Lucky and wire assemblies omitted. Accepted based on satisfactory local inspection.

	LIVISION	DOVER, NEW J	ERSTY	DIV		DIVISION
	Ars Opers	CERTIFIED TO AY:		Incpection		, INSPECTOR
PREPARED BY	D. Scoble					
LOT NO.	57-20	HOL-7-1435		- Offer	-	
DATE	1957	1955				
MFG'D BY	Budd Wheel Co.	Holston	6			
DRG. DATE OR REV.	unk a glack		11			
DRG NO.	Unk					
		Comp. B				
KIND	Parts Assy	Bursting				
COMPONENT	Metal	Che				

EXPERIMENTAL AMMUNITION DATA CARD NO. 95581 - LOT NO. PA-E-25559

00000 00 P-20-08 000	EXP	ERIMENTAL	AMMUNITION DA	ATA CARD	NO. 85754	
7 P 8 NO	END				AMM. LOT NO. PA-E-25674	
		Tetryl Fellets				
None	DAG DATE ON BEA	ALLOT ABVICE	PHOJECT NO	HADE OR EPO HO.	QUANTITY IN SHIPMENT	
3034.64	PROP CHARGE	EXPECTED IL V	ESPECTED PRESSURE	ASSCHOLES SH	May, 1957	

REMARKS: Packed: 18 Pellets/wrapped in commercial kraft paper and 17 pellets wrapped in commercial kraft paper/wood box/overpacked.

Dia, 1.25" - .03".

Height .500 - .03

Density GM/CC 7.55

	DIVISION	DOVER NEW JERSEY			DIVISION
	Ars Opers	PICATINNY ARSENAL GIG	Inspection		
PREPARED BY	D. Scoble	CERTIFIED TO BY:	ViG.		INSPECTOR
201 110	1414-470	42	od	-	
LOT NO	1945 ALA-956	134			
DATE	The state of the s	-64			
BATE LOT NO	Alabama				
DAG DATE OR REV					
D46 HO					
TIND					
COMPGNENT	Tetryl				

EXPERIMENTAL AMMUNITION DATA CARD NO. 85754 - LOT NO. PA-E-25674

DISTRIBUT	ON	APPENDIX D
NAME AND ADDRESS	NO. OF COPIES	AFG COPY NO. OF 13 Copies
Chief of Ordnance Washington 25, D. C. ATTN: ORDIN	1	3
Commanding Officer Diamond Ord Fuze Lab Washington 25, D. C.		
ATIN: Tech Ref Sec Commanding General Frankford Arsenal Philadelphia 37, Pa.	1	4
ATTN: ORDBA-MDR Commanding Officer	1	5
Picatinny Arsenal Dover, N. J. ATTN: ORDBB- Mr. Kuperman	1	6
Budd Company 2450 Hunting Park Ave. Philadelphia 32, Pa. THRU: Phila Ord District	1	7
Armed Services Tech Inf Agency Document Service Center Dayton 2, Ohio ATTN: TICSCP-2	l vellum	8
British Joint Services Mission 1800 K Street, N. W. Washington 6, D. C. ATTN: Reports Officer	2	0 - 10
Canadian Army Staff 2450 Mass. Avenue Washington 8, D. C.		9 - 10
ATTN: GSO-1, A&R Sec CONARC Liaison Ofcer	2	11 - 12
Aberdeen Proving Ground, Md. ATTN: Col. L. W. Linderer	1	13
Technical Library Branch Aberdsen Proving Ground, Md.	Original 1 Reference 1 Record	0 1 2

D-1